

AlumaPower™ Genuine Miller® Accessories



Industrial MIG 4/0 Kit with Dinse Connectors 300405

For AlumaPower 350 MPa power source. Includes flowmeter regulator with 10-foot (3 m) gas hose, 10-foot (3 m) 4/0 feeder weld cable with Dinse-style connector on one end and a lug on the other, 15-foot (4.6 m) work cable with Dinse-style connector on one end and 600-amp C-clamp on the other.

Industrial MIG 4/0 Kit 300390

For AlumaPower 450 MPa power source. Includes the same as the kit above, except weld and work cables have lugs instead of Dinse-style connectors.

Remote Control Extension Kits

- 242205025** 25 ft. (7.6 m)
 - 242205050** 50 ft. (15 m)
 - 242205080** 80 ft. (24.3 m)
- Fully loaded 14-pin extension cords for remote controls or 24 V and 115 V feeders.

Cable Connectors and Adapters

Note: AlumaPower 350 power sources are equipped with Dinse-style connectors for secondary connections.



Dinse/Tweco® Adapter 042465

Dinse/Cam-Lok Adapter 042466

One-piece adapter with Dinse-style male plug (to power source) on one end and female receptacle (Tweco or Cam-Lok for weld cable connection) on other end.

Dinse-Style Connector Kit

- 042418** Accepts #4 to #1/0 AWG cable size.
 - 042533** Accepts #1/0 to #2/0 AWG cable size.
- Kit includes one male Dinse-style plug which attaches to the work and/or weld cables and plugs into the Dinse-style receptacles on the power source.

Extension Kit for Dinse-Style Cable Connectors 042419

Accepts #4 to #1/0 AWG cable size. Used to adapt or extend weld and/or work cables. Kit includes one male Dinse-style plug and one in-line female Dinse-style receptacle.

AlumaFeed™ System Genuine Miller® Accessories

Remote Connector Kit 300898 Field Useful when pairing XR-AlumaFeed with an automated system. Allows remote trigger function, or remote voltage or arc length when used with XR-Aluma-Pro™ or XR™-Pistol guns and remote. See XR-Aluma-Pro literature M/1.73 or XR-Pistol literature M/1.71 for gun stock numbers.



Universal Carrying Cart and Cylinder Rack 042934

Holds power source, and gas cylinder up to 56 inches (142.2 cm) high measuring 6 to 9 inches (15.2 to 22.8 cm) in diameter.



Coolmate™ 4 042288 115 V

For use with water-cooled torches rated up to 600 amps. Tough molded polyethylene case with carrying handle.



MIGRunner™ Cart 195445

Small footprint and easily maneuverable, with cylinder rack low enough that you do not have to lift bottles.

Coolant Systems

For more information see literature AY/7.2.



Coolmate™ 3 043007 115 V
043008 230 V

For use with water-cooled torches rated up to 600 amps. Unique paddle-wheel indicator, external filter and easy-fill spout.

Coolant 043809

Sold in cases of four one-gallon recyclable plastic bottles. Miller coolants contain a base of ethylene glycol and deionized water to protect against freezing to -37 degrees Fahrenheit (-38° C) or boiling to 227 degrees Fahrenheit (108° C). Also contains a compound that resists algae growth.

AlumaFeed MIGRunner™



AlumaFeed 350 MIGRunner with 25-foot (7.6 m) air-cooled XR-Aluma-Pro gun shown.

- 951151** AlumaFeed 350 with 25 ft. (7.6 m) air-cooled XR-Aluma-Pro gun
- 951555** AlumaFeed 350 with 25 ft. (7.6 m) water-cooled XR-Aluma-Pro gun
- 951153** AlumaFeed 350 with 30 ft. (9 m) air-cooled XR-Pistol gun
- 951556** AlumaFeed 350 with 30 ft. (9 m) water-cooled XR-Pistol gun
- 951459** AlumaFeed 450 with 25 ft. (7.6 m) air-cooled XR-Aluma-Pro gun
- 951559** AlumaFeed 450 with 25 ft. (7.6 m) water-cooled XR-Aluma-Pro gun

Packages include:

- AlumaPower 350 or 450 MPa power source (350 MPa water-cooled packages and all 450 MPa packages have 115 V auxiliary power)
- XR-AlumaFeed wire feeder
- Air- or water-cooled XR-Aluma-Pro (gooseneck-style) or XR-Pistol (pistol-grip-style) push-pull gun
- MIGRunner cart
- Industrial MIG 4/0 MIG kit with Dinse connectors
- Gun and feeder drive rolls and consumables to run .035–3/64 inch (0.9–1.2 mm) wire (1/16-inch consumables not included, order separately)
- Coolmate 3 and coolant included with water-cooled packages