

# Genuine Miller® Accessories



Female Receptacle 

**Full KVA Adapter Cord 300517** Field  
NEMA 14-50P to NEMA 6-50R. Adapts engine drive 120/240 V plug to common Millermatic® and Spectrum® 240 V plug.



**Full KVA Plug Kit 119172** Field  
120/240 V, 50 A plug (NEMA 14-50P) to fit full KVA receptacle.

## Engine Filter Kits

**252782** Field. For Mitsubishi  
Includes all filters required for proper engine maintenance. Oil filter, primary and secondary fuel filter, and primary air filter.

**Spark Arrestor (Muffler) Kit 300585** Field  
Prevents particles from leaving the muffler that could potentially start a fire. Mandatory when operating on California grasslands, brush, or forest-covered land, and all national forests. For other areas, check your state and local laws. Meets U.S. Forest Service Standard 5100-1B.



**FA-1D Lockable Flame Arrestor Fuel Cap 043947** Field  
Fuel cap can be padlocked to prevent vandalism. A built-in flame arrestor prevents flames or sparks from entering the fuel tank.



**Protective Cover 195301** Field  
Blue water-resistant cover with Miller logo resists stains and mildew, and protects the finish of your welder.

## MIG (GMAW) or Flux-Cored (FCAW)



**SuitCase® X-TREME™ 8VS Wire Feeder 951583** With Bernard™ BTB Gun 300 A

**SuitCase® X-TREME™ 12VS Wire Feeder 951544** With Bernard™ Dura-Flux™ gun

Lightweight, voltage-sensing wire feeders include secondary contactor, gas valve, drive roll kit and gun. See literature M/6.42.




**SuitCase® 12RC Wire Feeder 951580**

Lightweight and flexible enough to run a variety of wires up to .062-inch diameter. Includes remote voltage control, drive roll kit and Bernard™ BTB Gun 300 A. See literature M/6.5.



**FieldPro™ Smart Feeder 300935**  
For use with Big Blue 350 PipePro SF model only. See page 2 for more information.



## PipeWorx Memory Cards

For use with FieldPro Smart Feeder only.

### 301230 System Software

For free download, visit MillerWelds.com

### 300557 Calibration

Used to calibrate the PipeWorx System. For free download, visit MillerWelds.com

### 300744 Inconel

Pulsed MIG, .045-inch diameter wire, 100% argon

### 300460 Range Locks

Provides ability to set nominal parameter values and ranges for wire feed processes.

### 300667 Accu-Power™

Displays instantaneous power during welding to meet the new ASME requirement for calculating heat input on complex waveform processes (RMD® and pulsed MIG).

### 301035 Trigger Select/Hold Option

Enables trigger select while welding to change processes and parameters without stopping.

## TIG (GTAW) Welding



### Dynasty® 210 Series 907685, 907686

For premium portable AC/DC TIG arc quality. See literature AD/4.81.



### HF-251D-1 042388

115 V. High-frequency arc starter and stabilizer. See accessory literature AY/5.0.