

ACE INDUSTRIAL PRODUCTS
5043 Farlin Avenue
St. Louis, MO 63115
www.aceindustrialproducts.com

Phone: 314-679-2540
Fax: 314-385-5178



Model 73-201-95 & 73-201-HEPA	Portable Fume Extractor
<p>Ace Industrial Products of St. Louis, MO. manufactured self contained, high vacuum fume extractor constructed of 14 and 16 gauge powder coated semi gloss finish, cold rolled steel. Unit capable of exhausting 113 and 226 CFM with filters in place through two 7 amp, 120v single phase vacuum motors. Unit includes built in spark trap and accepts 1" of pre-filtration with a minimum of 3.2 square feet of filter media and main filter with a minimum of 53 square feet of filter media. Unit includes 10 feet of flexible extraction hose, 28" flexible steel extraction tube with 12" slot nozzle and magnetic base, LED filter status light, carry handle,</p>	
Motor	Quantity 2: 7 Amp 120 Volt Single Phase
Airflow	113 cfm (Low) and 226 cfm (High)
Decibels	<85 db
Construction	14 & 16 GA. Cold Rolled Steel w/ finger latching, gasketed filter access
Length	24"
Height	17"
Width	12"
Weight	44 lbs. without filters, 58 lbs. with filters installed
Capture	10 foot flexible hose, 12" slot nozzle on flexible tube with magnetic base
Primary Pre Filter	12" x 12" x 1" Multi-Pleat, Cotton / Synthetic Media, 3.2 Sq. Ft media surface rated at 40% ASHRAE efficiency (alternatives available – consult filter and parts guide)
Primary Main Filters	<p>73-201-95 - 12" x 12" x 11.5" High Capacity Multi-Pleat in Particle Board Frame, 53 sq. ft. media surface rated at 95%@5 microns ASHRAE efficiency, MERV 15 (alternatives available – consult filter and parts guide). Filter applicable for use on carbon steel processes, aluminum, stainless steel, and galvanized steel.</p> <p>73-201-HEPA - 12" x 12" x 11.5" High Capacity Multi-Pleat in Particle Board Frame, 53 sq. ft. media surface rated at 99.97%@.3 microns ASHRAE efficiency, MERV 15 (alternatives available – consult filter and parts guide). Filter applicable for use on carbon steel processes, aluminum, and stainless steel.</p>
Flammability	Class 2, UL Standard 900
Options	Dual Operator T- Connector
Warranty	Two Year Limited
Source	Made in USA (St. Louis, MO)

Specifications subject to change without notice.